

MK200

Micro Kiosk



Introducing the perfect price checker to improve your customer experience and business efficiency!

The MK200 price inquiry terminal features a 10-inch touchscreen and the Android 11 operating system, providing a modern, agile and customizable interface. Its RK3568 processor, along with 4GB of RAM and 32GB of internal storage, ensures smooth performance for performing multiple tasks simultaneously.

With Wi-Fi, Bluetooth and PoE (Power over Ethernet) connectivity, this micro kiosk is extremely versatile, allowing it to be used without additional cables for power. It is also VESA compliant and includes a mounting bracket, making it easy to install on walls or columns.

The integrated barcode reader is a comprehensive solution for fast and accurate price queries, with the ability to read 1D and 2D codes. Due to its front orientation, it simplifies the reading of large and difficult-to-handle products, providing a more comfortable and faster experience for both the customer and the store staff.

With integrated speakers, this consultation terminal allows not only to display information on the screen, but also to emit audio notifications or personalized messages, improving interaction with the client.

Optimize the shopping experience and improve customer service with this powerful price inquiry solution. It's the tool you need to modernize and streamline your points of sale!

- PoE Ethernet port
- 2D Imager Barcode Scanner
- 10.1" capacitive screen



Technical Specifications

PERFORMANCE

Processor
RK3568 4 Cores 2.0Ghz
Operating System
Android 11
Memory
4GB RAM
32GB ROM
Screen
10.1" TFT-LCD Panel, capacitive touch
Resolution
1280 x 800
Speakers
Speakers: 2 x 2W 8ohm
Wireless connectivity
Wi-Fi 802.11b/g/n 2.4Ghz
Bluetooth 4.0

ENERGY

Energy consumption
Operating: 15W (typical)
Off: 0W
Input power specifications
AC 100-240Vac, 1.5A 50-60Hz, DC
12V±5% 2A Max.

PHYSICAL CHARACTERISTICS

Dimensions
253mm x 163mm x 29mm
Weight
825grs
Interfaces
1x USB 3.0 Type A
1x USB 2.0 Debug Port
1x HDMI
1x SDHC expansion slot
1x RJ45 Ethernet
1x PoE
1x DC-IN 12V 2.1mm
1x Headphone jack
VESA
VESA 75 x 75mm compatible
Includes VESA bracket for mounting
Construction
ABS structure and touch screen with tempered glass.
Color
Black

ENVIRONMENTAL

Operating temperature
0 to 40°C
Storage temperature
-10 to 50°C
Humidity
10% to 85% (non-condensing)

DATA CAPTURE

Scanner
1D/2D imager, vertically oriented, with 60° frontal angle.
Read codes from screens.
1D
All the main symbologies, including UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, GS1 Composite Code, Code 11, Industrial 25, Standard 25, Plessey, Matrix 2 of 5
2D
All major symbologies including QR Code, Data Matrix, PDF417, Micro PDF417, Aztec, Maxicode, Micro QR

